

Features

- Up to 20 personal memory slots
- Time, date and day of the week display
- Time and date stamping
- Unread message reminder alert
- Delete all read and unlocked messages
- Protect up to 10 messages
- Battery low indicator
- Out-of-range indicator
- Duplicate message indication
- Continuous message indication
- Memory full indication
- Error message indication
- Back light
- Memory retention
- 1 alarm
- Vibrate/9 pleasing/vibrate then audible/no alert
- Quick browse of first screen messages

Synthesized POCSAG Numeric Pager



Specifications

Model no.	BRAVO 500	
Frequency:	VHF (135 - 175MHz), UHF (452-468MHz), 900MHz (929-932MHz)	
Channel Spacing:	25 kHz	
Frequency Deviation:	+/- 4.5 kHz	
Paging Sensitivity:	VHF/UHF	900MHz
EIA Selectivity:	55 dB	40 dB
EIA Spurious and Image:	50 dB	40 dB
IM Rejection:	50 dB	40 dB
Operating Temperature:	-10°C to 50°C	5°C to 40°C
Alert Tone Loudness:	75 dB @ 12 inches	
Battery Type:	1 x Alkaline AA	
Battery Life:	~35 days (for 1200 bps)	
Weight (with battery):	45 grams	
Dimensions:	55 x 41 x 16 mm	

RAD DEV FOR HAZ LOC INT SAFE
CI.I,Div1,Gr.ABCD;CI.II,Div2,Gr.FG

